



Styrok®

BETTER THAN STONE

T-ROK EXTERIOR PANELS

PRODUCT DESCRIPTION

The T-Rok is a durable, lightweight, exterior wall panel that emulates rich texture and colour of smooth natural stone.

We individually cast each panel by pouring 1/8" of glass fibre reinforced concrete (GFRC), fine aggregate and natural colour pigment into highly-detailed moulds.

The panels contain a 1" EPS (foam) core. As a result, they weigh under 2 lbs per square foot and can be installed quickly and easily without any structural support. They also provide R-value insulation of 4(+).

Note: the EPS we use meets or exceeds the CAN/ULC S701 standard for polystyrene.

PRODUCT USE

T-Rok Panels are designed for exterior applications. They are suitable for residential or commercial projects and can be installed over new or existing construction.

DIMENSIONS

- Size: 16" x 24"
- Weight: under 2 lbs per sq ft
- Thickness: 1 1/8"

INSTALLATION

T-Rok's can be installed over new or existing construction. For new construction, they are applied over an EIFS system. No mechanical fastening or structural support is required. For detailed installation instructions, please see the "T-Rok Panel Installation Guide", found on our website.

MAINTENANCE

T-Rok Panels come pre-sealed and are made of moisture resistant GFRC. As a result, they do not require any finishing and will not absorb dirt or dust. If any dirt accumulates on their surface, they can be safely power washed.

LIMITED WARRANTY

T-Rok Panels come with a five year limited warranty. Contact us for more information.

SAFETY / HANDLING

Until T-Rok's are installed on a wall, they should be handled with care to avoid cracking - do not throw or step on them. They can be stored by stacking one on top of the other.

STYROK INC.

452 Bowes Road, Unit 7-10, Concord, ON, L4K 1K2
905.760.0580 / 416.824.2886 - info@styrok.com